

Formulas

Measurement unit abbreviations

fpr	feed per revolution
fpt	feed per tooth
rpm	revolutions per minute
tpi	threads per inch

Constants

π	3.1416
-------	--------

Formulas

Descriptions	Full	Abbreviated
Bend allowance (for 90° bend)	$(\text{radius} + (0.4 \times \text{thickness})) \times 1.5708$	$(r + (0.4 \times T)) \times 1.5708$
Cutting force	$\text{length} \times \text{thickness} \times \text{shear strength}$	$L \times T \times S$
External thread depth (imperial)	$0.6134 \times \text{pitch}$	$0.6134 \times P$
Feed rate per minute	$\text{feed per tooth} \times \# \text{ teeth}$ $\times \text{revolutions per minute}$	$\text{fpt} \times N \times \text{rpm}$
Internal thread depth (imperial)	$0.5413 \times \text{pitch}$	$0.5413 \times P$

Formulas (continued)

Measurement over wires	major diameter + (3 × wire diameter) – $\left(\frac{1.5155}{\text{threads per inch}} \right)$	MD + (3 × WD) – $\left(\frac{1.5155}{\text{tpi}} \right)$
Measurement over wires	pitch diameter – (0.866025 × pitch) + (3 × wire diameter)	PD – (0.866025 × P) + (3 × WD)
Pitch diameter (metric)	major diameter – (0.6495 × pitch)	MD – (0.6495 × P)
Revolutions per minute (imperial)	$\frac{12 \times \text{cutting speed}}{\pi \times \text{diameter}}$	$\frac{12 \times \text{CS}}{\pi D}$
Revolutions per minute (metric)	$\frac{1\,000 \times \text{cutting speed}}{\pi \times \text{diameter}}$	$\frac{1\,000 \times \text{CS}}{\pi D}$
Tap drill size	major diameter – pitch	MD – P
Time (for lathe)	$\frac{\text{length}}{\text{feed per revolution} \times \text{revolutions per minute}}$	$\frac{L}{\text{fpr} \times \text{rpm}}$
Time (for mill)	$\frac{\text{length}}{\text{feed per tooth} \times \# \text{ teeth} \times \text{revolutions per minute}}$	$\frac{L}{\text{fpt} \times N \times \text{rpm}}$
Wire size	0.57735 × pitch	0.57735 × P